Find the Right Bullhorn for Your Application

Remote Monitoring System:	RM510	RM520	RM540	RM4210/4250
Application	Rectifier	Bonds	Test Point	AC Monitoring
Analog Channels	4 (16 w/ Expansion Module)	3	2	5
Digital Channels	2	n/a	n/a	n/a
Typical Measurements	✓ Rectifier Volts ✓ Rectifier Amps ✓ Pipe-to-Soil ✓ Instant Off	✓ Pipe-to-Soil ✓ Bond Negatives ✓ IR Free Instant Off ✓ Bond Current	✓ Pipe-to-Soil ✓ Bond Negatives ✓ IR Free Instant Off	✓ AC Current Density ✓ DC Current Density ✓ Pipe-to-Soil ✓ Drain Current ✓ IR Free Instant Off
Interruption	Yes	Yes (Bond)	No (Interruption Aware)	Yes (Coupon)
Communication Network	Two-Way Cellular: AT&T Satellite: Iridium	Two-Way Cellular: AT&T Satellite: Iridium	Two-Way Cellular: AT&T Satellite: Iridium	Two-Way RM4210: Orbcomm Satellite RM4250: Cellular
Mounting	Internal/External	Test Head	Test Head	Test Head Flat-Base
Surge Protection/Rating	30kV System Surge	In-circuit Protection Solid State Relay	In-circuit Protection	In-circuit Protection
Power Source	Line or Secondary Rectifier Taps	Replaceable Battery	Replaceable Battery	Replaceable Battery
Backup Power	Battery	No	No	Solar (Optional)
Warranty	3 Year All Inclusive	3 Year All Inclusive	3 Year All-Inclusive	Standard
Data Security	Bullhorn Web Security	Bullhorn Web Security RMU Security Pin	Bullhorn Web Security RMU Security Pin	Bullhorn Web Security